Cooper Lighting and Safety Ltd Wheatley Hall Road, Doncaster, South Yorkshire, DN2 4NB Tel: +44 (0) 1302 303999 Fax: +44 (0) 1302 303333

Fax: +44 (0) 1302 303333 Emai: info@cooperfire.co.uk Web: www.cooperfire.com



DECLARATION OF PERFORMANCE

DoP0024

Product(s) Identification Code:
BiWire Ultra Range of Control and Indicating Equipment
Type, Batch or serial numberor any other elementallowing identification of the construction products(s) as required pursuant to Article 11(4): EFBW2ZONE, EFBW4ZONE, EFBW8ZONE, FXPBW2ZONE, FXPBW4ZONE, FXPBW8ZONE, UBBW4ZONE, UBBW8ZONE
Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as forseen by the manufacturer:
Fire detection and fire alarm systems
Name, registered trade name or registered trade mark and contact address of the manufactureras required pursuant to Article 11(5):
Eaton Industries Manufacturing GmBH, Electrical Sector EMEA, Route de la Longeraie 7, 1110 Morges, Switzerland
Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): Not Applicable
Tvot / ipprication
System or systems of assessment and verification of constancy of performance of the construction product as set out in AnnexV: System 1
In case of the declaration of performance concerning a construction product covered by the harmonized standard: Intertek Tesing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB, United Kingdom
performed type testing and the initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system 1 and issued the EC certificates of conformity: 0359-CPR-00450

Cooper Lighting and Safety Ltd Wheatley Hall Road, Doncaster, South Yorkshire, DN2 4NB Tel: +44 (0) 1302 303999

Fax: +44 (0) 1302 303333 Emai: info@cooperfire.co.uk Web: www.cooperfire.com



Declared performance:

All requirements including all Essential Characteristics and the corresponding performances for the intended use or uses indicated in point 3 above have been determined as described in the hEN mentioned in the table below.

Essential Characteristics	Performance	Harmonized Technical Specification	
			EN54-4:1997
		EN54-2: 1997+A1:2006	+A1:2002+A2:2006
Performance under fire conditions	Pass	4,5,7	-
Operational reliability	Pass	4,5,6,7,8,9,10,11,12,13,14	4,5,6,7,8
Durability Of Operational Reliability,	Pass	15.4	9.5
Temperature Resistance			
Durability of Operational Reliability,	Pass	15.5,15.14	9.6, 9.14
Humidity Resistance			,
Response delay (response time to fire)	Pass	4,5,6,7,8.9,10,11,12,13,14	_
Durability Of Operational Reliability, Shock and Vibration Resistance	Pass	15.6, 15.7, 15.15	9.7, 9.8, 9.15
Durability Of Operational Reliability, Electrical Stability	Pass	15.8 to 15.13	9.9 to 9.13
Durability Of Operational Reliability, Resistance to Ingress	Pass		-

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of Eaton Industries Manufacturing GmBH by:

2nd October 2015, Cwmbran

Date and Place of Signature

Mr Phil Williams, Certification Manager

9:1